

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

This is to certify:**That the NAVTEX receiver**with type designation(s)
NVX-1000, NVX-3000


Issued to

**New Sunrise Co.,Ltd.
Suzhou, Jiangsu, China**

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2018/773,****item No. MED/5.3. SOLAS 74 as amended, Regulations IV/7, IV/14 & X/ 3, IMO Res A.694(17), IMO Res. MSC.36(63), IMO Res. MSC.97(73), IMO Res. MSC.148(77), IMO COMSAR Circ.32, ITU-R M.540-2 (06/90), ITU-R M.625-4 (03/12), MSC.302(87), MSC.430(98)**

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2024-07-29**.Issued at **Hamburg** on **2019-07-30**DNV GL local station:
Shanghaifor **DNV GL SE**Approval Engineer:
Harald BluhmNotified Body
No.: **0098****Gerhard Aulbert**
Head of Notified Body

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

The NAVTEX receiver NVX-1000 / NVX-3000 consists of the following equipment:

Mandatory equipment		
No.	Description:	Type:
1	Main/Operator unit	NVX-1000 or NVX-3000 Main unit
2	Antenna Amplifier	NVX-1070F
3	Whip Antenna	NXA100/NXA200
Software		
4	NVX-1000	Version 1.xx
5	NVX-3000	Version 1.xx
Optional equipment		
6	Thermal Printer	NPT-100
7	Power Supply 24VDC Output	

Manuals:

User Manual NAVTEX Receiver NVX-3000 NVX-3000 UM.E 20190506-01
 User Manual NAVTEX Receiver NVX-1000 NVX-1000 UM.E 20190510-04

Type Examination documentation

Performance Testreport	IEC 61097-6 Ed.2.1(2012) IEC 60945 general part IEC 61162-1, -2	NSR-NVX1000-Test190516P, NSR-NVX3000-Test190516P
Environmental / EMC Testreport	IEC 60945	A19-013-WT-01, A19-013-WT-02

Tests carried out

IEC 60945 (2002) incl. IEC 60945 Corr. 1 (2008),
 IEC 61097-6 (2012-01).

Marking of product

According to Article 10 of the Council Directive (MED):

- The wheel mark shall be affixed visibly, legibly and indelibly to the product or to its data plate and, where relevant, embedded in its software. Where that is not possible or not warranted on account of the nature of the product, it shall be affixed to the packaging and to the accompanying documents.
- The wheel mark shall be affixed at the end of the production phase.
- The wheel mark shall be followed by the identification number of the notified body, where that body is involved in the production control phase, and by the year in which the mark is affixed.
- The identification number of the notified body shall be affixed by the body itself or, under its instructions, by the manufacturer or the manufacturer's authorised representative.

For specific products, manufacturers may use an appropriate and reliable form of electronic tag instead of, or in addition to, the wheel mark.

Each unit of equipment normally to be installed in a distance of 5 m or less from a standard or a steering magnetic compass shall be clearly marked with the minimum safe distance at which it may be mounted from such compasses.

Only for fixed equipment: Alternatively, the minimum safe distance may be given in the equipment manual.

END OF CERTIFICATE